



CONSTRUCTION:

Basin-mounted soap dispenser has polyethylene globe. Units are designed to be filled from the top for easy maintenance. 4" (102mm) long spout directs soap flow over sink. Exposed portions are chrome-plated brass to match the existing faucets.

CAPACITY:

8-1/4" (210mm) globe - 32-fl oz. (0.9-L)

OVERALL DIMENSIONS:

Unit requires 1" (25mm) hole in the vanity or basin.

MOUNTING:

Mounting location for push button dispensers are 44" (1118mm) maximum above the finish floor.

INSTALLATION:

Unit is typically located adjacent to a flush mounted sink through .875"-1" (22-25mm) dia. cut out (by others) in counter top. An adjustable threaded shank allows for installation in counter tops up to 3-1/2" (89mm) thick.

ADA GUIDE:

Push buttons and pistons should be operable with one hand and without tight grasping, pinching, or twisting of the wrist. Activation of soap valves should not require more than 5 pounds of force when unit is completely filled. Spout shall rotate 360° without damage to valve mechanism.

NOTE:

Soap dispenser shall dispense liquid lotion soaps, and synthetic detergents.

Basin-Mounted Soap Dispenser with All-Purpose Valve shall be Model G-64LB of Gamco Commercial Restroom Accessories, One Gamco Place, Durant, OK, 74701-1910